

# **Drill Driver CXT® DF333D**

12V max • 30 Nm • 0 − 1 700 min<sup>-1</sup>

#### Light tool for drilling and screwdriving

A compact tool for drilling and screwdrivers for fitters and maintenance staff and for home use. Thanks to its small size, the tool is easy to use and offers access to tight places. A max. torque of 30 / 14 Nm and two speed ranges.





### **Technical specifications**

**CXT Battery** No load speed min<sup>-1</sup> Max. fastening torque Hard/Soft 30 / 14 Nm 20 Torque setting Max. Drilling Diameter in Wood 21 mm Max. Drilling Diameter in Steel 10 mm **Drill Chuck Capacity** 0.8 - 10 mm Sound Pressure Level (L<sub>DA</sub>) 71 dB(A)

Noise Uncertainty (K Factor) 3 dB(A) Tool weight with battery 1,1 - 1,2 kg Nominal Battery Voltage 12 V Battery Chemistry (Ni-Cd / Ni-MH / Li-Li-ion

Drilling Capacity Wood (Self-feed bit) **Driving Shank** 

Vibration Level, Drilling into metal Vibration Uncertainty (K Factor),

0 - 450 / 0 - 1700

42 mm

3/8 "

 $\leq$  2,5 m/s<sup>2</sup>

1.5 m/s<sup>2</sup>

#### **User benefits**

- Compact and lightweight for reduced operator fatigue
- · LED light illuminates the work site
- Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makitauk.com



## **Related products**

## Optional AC

251314-2

Truss Head Screw M4\*12, Td140D

346909-5 Belt Hook

Ei

456128-6

Battery Cover CXT®



784244-7

Screw Bit, Ph2 - Ph2, 50 Mm, Double



**Other** 

**User manual** 

**Parts drawing**