



## 2 Piece Combo Kit LXT®

# DLX2134TJ

18V

Includes : DJV180 Jigsaw and DHP482 Combi Drill.



### Models in kit



**Combi Drill LXT®**  
**DHP482**



**Jigsaw LXT®**  
**DJV180**



## Combi Drill LXT®

### DHP482

18V • 62 Nm • 0 – 1 900 min<sup>-1</sup>

**Powerful general-use combi drill with hammer action for professionals**

An efficient drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 62 / 36 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light.



**LXT**

#### Technical specifications

|                                            |                                    |
|--------------------------------------------|------------------------------------|
| Nominal Battery Voltage                    | 18 V                               |
| Voltage LXT                                | ✓                                  |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion                             |
| No load speed                              | 0 - 600 / 1900 min <sup>-1</sup>   |
| Max. fastening torque Hard/Soft            | 62 / 36 Nm                         |
| Max Torque                                 | 64 Nm                              |
| Torque setting                             | 21                                 |
| Impacts per Minute (IPM)                   | 0 - 9000 / 28500 min <sup>-1</sup> |
| Max. Drilling Diameter in Masonry          | 13 mm                              |
| Max. Drilling Diameter in Concrete         | 13 mm                              |
| Max. Drilling Diameter in Steel            | 13 mm                              |
| Drilling Capacity Wood (Auger Bit)         | 38 mm                              |
| Drilling Capacity Wood (Self-feed bit)     | 51 mm                              |
| Drilling Capacity Flat bit                 | 38 mm                              |
| Drilling Capacity Hole Saw                 | 51 mm                              |
| Driving Shank                              | 1/2"-20UNF "                       |

#### User benefits

- Highly efficient and compact machine for professional use
- Battery protection system automatically shuts off power when the battery level is low
- Optimal handle design
- LED light illuminates the work site
- Ergonomic handle for easy manoeuvring

Link to product - [www.makitauk.com](http://www.makitauk.com)



# Jigsaw LXT®

## DJV180

18V • 0 – 2 600 min<sup>-1</sup>

### Efficient jigsaw with tool-less blade change

An efficient saw with three-stage pendulum action and tool-less blade change. Engine speed can be adjusted between 0 and 2 600 min<sup>-1</sup> from a switch to suit the material. A stroke length of 26 mm and cutting capacity of 135 mm in wood and 10 mm in steel.



**LXT**

### Technical specifications

|                                                       |                            |
|-------------------------------------------------------|----------------------------|
| Voltage LXT                                           | ✓                          |
| Nominal Battery Voltage                               | 18 V                       |
| Strokes per Minute (SPM)                              | 0 - 2600 min <sup>-1</sup> |
| Length of Stroke                                      | 26 mm                      |
| Max. Cutting Capacity in Wood (90°)                   | 135 mm                     |
| Max. Cutting Capacity in Steel (90°)                  | 10 mm                      |
| Capacity Aluminium                                    | 20 mm                      |
| Orbital Action                                        | ✓                          |
| Tool weight with battery                              | 2,7 - 3,0 kg               |
| Product Dimensions (L x W x H):                       | 257 x 73 x 208 mm          |
| Max. Bevel Range (Left)                               | 0 - 45 °                   |
| Vacuum cleaner connection Ø in / out                  | 25 / 31 mm                 |
| Vibration Level, Cutting Boards                       | 7,0 m/s <sup>2</sup>       |
| Vibration Uncertainty (K Factor), Cutting Boards      | 1,5 m/s <sup>2</sup>       |
| Vibration Level, Cutting Sheet Metal                  | 3,5 m/s <sup>2</sup>       |
| Vibration Uncertainty (K Factor), Cutting Sheet Metal | 1,5 m/s <sup>2</sup>       |

### User benefits

- 3 orbital settings
- The rubber coating on the handle ensures a firm working grip
- Tool-less blade change for fast blade installation and removal
- LED light illuminates the work site
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - [www.makitauk.com](http://www.makitauk.com)



# Related products kit

## Standard AC

142336-2

Connector P.Case Type4

346317-0

Belt Hook

417852-6

Cover Plate

687328-9

Band

784637-8

Screw Bit, Ph2 – S6, 45 Mm, Double

251314-2

Truss Head Screw M4\*12, Td140D



415524-7

Anti-splintering device



417853-4

Dust nozzle Ø 18 / 22 mm

783202-0

Hex Wrench 4Mm



B-06292 (2x)

Jig Saw Blade Set



## Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



## Optional AC

821552-6

Makpac case (4)



## Other - DHP482

User manual

Parts drawing

## Other - DJV180

User manual

Parts drawing