



2 Piece Combo Kit LXT®

DLX2145TJ

18V

Includes : DHP458 Impact Driver and DTD152 Impact Driver



Models in kit



**Combi Drill LXT®
DHP458**



**Impact Driver LXT®
DTD152**

Combi Drill LXT®

DHP458

18V • 91 Nm • 0 – 2 000 min⁻¹

Rugged combi drill for heavy-duty screwdriving and drilling

A powerful drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 91 / 58 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light.



LXT

Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 400 / 2000 min ⁻¹
Max. fastening torque Hard/Soft	91 / 58 Nm
Max Torque	110 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 6000 / 30000 min ⁻¹
Max. Drilling Diameter in Masonry	16 mm
Max. Drilling Diameter in Steel	13 mm
Drilling Capacity Wood (Auger Bit)	50 mm
Drilling Capacity Wood (Self-feed bit)	76 mm
Drilling Capacity Flat bit	40 mm
Drilling Capacity Hole Saw	152 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm

User benefits

- With impact mode, the tool can be used for drilling stone materials.
- Battery level indicator
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.com



Impact Driver LXT®

DTD152

18V • 1/4" • 165 Nm • 0 – 2 900 min⁻¹

Compact impact driver for quick driving

A compact and light impact wrench with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 165 Nm, suitable for quick driving. A handy LED light for added lighting.



LXT

Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 2900 min ⁻¹
Max Fastening Torque Impact Drill	165 Nm
Impacts per Minute (IPM)	0 - 3500 min ⁻¹
Tightening Capacity Standard Bolt	M5 - M16
Driving Shank	1/4 "
Sound Power Level (L _{WA})	104 dB(A)
Sound Pressure Level (L _{pA})	93 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Impact Tightening of Fasteners of the Maximum Capacity of the Tool	10,5 m/s ²
Vibration Uncertainty (K Factor),	1,5 m/s ²

User benefits

- The rubber coating on the handle ensures a firm working grip
- LED light illuminates the work site
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- The screw tip is securely held in place by a quick lateral stroke
- Quick mount for 1/4 "screwdriver
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.com



Related products kit

Standard AC

821551-8

Makpac case (3)



122576-8

Stopper Pole



123257-7

Side Handle



251314-2 (2x)

Truss Head Screw M4*12, Td140D



266622-8

Truss Head Screw M4 X 12



346317-0 (2x)

Belt Hook



452947-8

Bitholder



784637-8 (2x)

Screw Bit, Ph2 – S6, 45 Mm, Double



Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



Optional AC

821551-8

Makpac case (3)



Other - DHP458

User manual

Parts drawing

Other - DTD152

User manual

Parts drawing