



2 Piece Brushless Combo Kit LXT®

DLX2414ST

18V

Includes: DHP487Z Brushless 18V Combi Drill and DTD157Z
Brushless 18V Impact Driver



Models in kit



Combi Drill LXT®
DHP487



Impact driver LXT®
DTD157

Combi Drill LXT®

DHP487

18V • 40 Nm • 0 – 1 700 min⁻¹

A powerful, brushless general-use impact drill for screwdriving and drilling

A powerful, brushless general-use impact drill for screwdriving and drilling



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Brushless Motor	✓
No load speed	0 - 500 / 1700 min ⁻¹
Max. fastening torque Hard/Soft	40 / 25 Nm
Max Torque	40 Nm
Torque setting	20
Impacts per Minute (IPM)	0 - 7500 / 25500 min ⁻¹
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Steel	13 mm
Drilling Capacity Wood (Auger Bit)	36 mm
Drilling Capacity Wood (Self-feed bit)	35 mm
Drilling Capacity Flat bit	36 mm
Drilling Capacity Hole Saw	51 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Electronic brake	✓

User benefits

- LED light illuminates the work site
- Highly efficient and compact machine for professional use
- Battery protection system automatically shuts off power when the battery level is low
- Electronic overload protection protects the user and the device
- Ergonomic soft grip handle provides increased comfort

Link to product - www.makita.com



Impact driver LXT®

DTD157

18V • 1/4" • 140 Nm • 0 – 3 000 min⁻¹

Extra-compact brushless impact driver with assist mode and three power settings for quick driving.

A compact and light impact wrench with a hex. 1/4" drive shank. A compact tool with a max. torque of 140 Nm. 3-mode operation for A-mode / Hard mode / Soft mode for multiple applications. Handy LED light.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Brushless Motor	✓
No load speed	0 - 1300 / 3000 min ⁻¹
Max Fastening Torque Impact Drill	140 Nm
Impacts per Minute (IPM)	0 - 2000 / 4100 min ⁻¹
Tightening Capacity Standard Bolt	M5 - M14
Driving Shank	1/4 "
Sound Power Level (L _{WA})	106 dB(A)
Sound Pressure Level (L _{pA})	95 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Impact Tightening of Fasteners of the Maximum Capacity of the Tool	11,5 m/s ²
Vibration Uncertainty (K Factor), Impact Tightening of Fasteners of the	1,5 m/s ²

User benefits

- Brushless motor is electronically controlled to optimise battery energy use for longer run time per charge
- LED light illuminates the work site
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Anti wobbling bit structure
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.com



Related products kit

Standard AC

821599-0

Plastic Carrying Case



Optional AC

B-49432

Drill Bit Set, TCT, M-Force, 18 pcs



D-72849

Metal drill bit set HSS-TiN, 10 pcs



D-72861

Wood drill bit set, 5 pcs



D-72877

Drill bit set T.C.T, 5 pcs



Other - DHP487

User manual

Parts drawing

Other - DTD157

User manual

Parts drawing