

3 Piece Combo Kit LXT®

DLX3049PTJ

18V

Includes : DHR264 Rotary Hammer, DTD152 Impact Driver,
DHS710 Circular Saw



Models in kit



**Rotary Hammer LXT®
DHR264**



**Circular Saw LXT®
DHS710**



**Impact Driver LXT®
DTD152**

Rotary Hammer LXT®

DHR264

18V X2 • SDS-PLUS • 26 mm • 2.5 J

Three-mode rotary hammer with quick-change chuck

An efficient rotary hammer with anti-vibration rear and side handles, for SDS-PLUS bits. Suited to impact and unstressed drilling and chipping. Speed range of 0 – 1 200 min⁻¹. Impact energy of 2.5 J and max. drilling capacity of 26 mm in concrete. .



Technical specifications

Nominal Battery Voltage	2 x 18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Impact Energy	2,5 J
Optimum Drilling Diameter Range in Concrete	4 - 18 mm
Max. Drilling Diameter in Concrete	26 mm
Max. Drilling Diameter in Wood	32 mm
Max. Drilling Diameter in Steel	13 mm
Impacts per Minute (IPM)	0 - 5000 min ⁻¹
No load speed	0 - 1250 min ⁻¹
Drilling diameter with TCT core bit	54 mm
Adapted for SDS-PLUS bits	✓
Tool weight with battery	3,5 - 4,7 kg
Vibration Level, Hammer Drilling Into Concrete	16,5 m/s ²

User benefits

- 36V performance from two 18V batteries connected in series. The batteries are placed in parallel in separate battery docking stations.
- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- One touch sliding chuck enables quick and easy bit changes
- Ergonomic chassis design ensures a good working position.
- Reversing switch
- LED light illuminates the work site
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - www.makita.com



Circular Saw LXT®

DHS710

18V X2 • 4 800 min⁻¹ • 190 mm

Robust saw for heavy-duty professional use

A robust wood-cutting circular saw for professional use with two LXT® 18V batteries that offer an output of 36V. A solid aluminium table that can be tilted to an angle of 50°. A blade diameter of 190 mm that offers a maximum cutting depth of 68,5 mm. Compatible with a guide rule.



■ Technical specifications

Nominal Battery Voltage	2 x 18 V
Voltage LXT	✓
Max. Cutting Depth at 90°	68,5 mm
Max. Cutting Depth at 45°	49 mm
Max. Cutting Depth at 50°	44 mm
No load speed	4800 min ⁻¹
Sound Power Level (L _{WA})	105 dB(A)
Sound Pressure Level (L _{pA})	97 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	3,9 - 4,6 kg
Product Dimensions (L x W x H):	356 x 217 x 298 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Max. Bevel Range (Right)	0 - 50 °
Blade Diameter	190 mm

■ User benefits

- Rigid aluminium base provides smooth cutting thanks to its lightness, toughness and good bend resistance
- Battery protection system automatically shuts off power when the battery level is low
- The rubber coating on the handle ensures a firm working grip

[Link to product - www.makita.com](http://www.makita.com)



Impact Driver LXT®

DTD152

18V • 1/4" • 165 Nm • 0 – 2 900 min⁻¹

Compact impact driver for quick driving

A compact and light impact wrench with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 165 Nm, suitable for quick driving. A handy LED light for added lighting.



LXT

Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 2900 min ⁻¹
Max Fastening Torque Impact Drill	165 Nm
Impacts per Minute (IPM)	0 - 3500 min ⁻¹
Tightening Capacity Standard Bolt	M5 - M16
Driving Shank	1/4 "
Sound Power Level (L _{WA})	104 dB(A)
Sound Pressure Level (L _{pA})	93 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Impact Tightening of Fasteners of the Maximum Capacity of the Tool	10,5 m/s ²
Vibration Uncertainty (K Factor),	1,5 m/s ²

User benefits

- The rubber coating on the handle ensures a firm working grip
- LED light illuminates the work site
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- The screw tip is securely held in place by a quick lateral stroke
- Quick mount for 1/4 "screwdriver
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.com



Related products kit

Standard AC

164095-8
Parallel Guide



196520-1
Dust Nozzle



324219-0
Depth Gauge



443122-7
Cleaning Cloth



783217-7
Hex Wrench 5Mm



821552-6 (2x)
Makpac case (4)



194079-2
Quick Change Drill Chuck 13 mm,



266622-8
Truss Head Screw M4 X 12



346317-0
Belt Hook



450128-8 (4x)
Battery cover, LXT®, 14,4 – 18V



821551-8
Makpac case (3)



Standard MA

BL1850B (4x)
Battery LXT® 5,0 Ah



DC18RD
Battery Charger LXT®



Optional AC

821551-8
Makpac case (3)



821552-6 (2x)
Makpac case (4)



Other - DHR264

User manual

Parts drawing

Other - DHS710

User manual

Parts drawing

 **Other - DTD152**

User manual

Parts drawing